

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Frequency Converter**with type designation(s)
Emotron VFX 2.0

Issued to

CG Drives & Automation Sweden AB
Helsingborg, Sweden

is found to comply with

DNV GL rules for classification – Ships, offshore units, and high speed and light craft**Application :****Frequency Converter for Asynchronous Motors Emotron VFX 2.0 series.**
Range: 0.75/0.55 kW to 3000/2400 kW, 230 - 690 VAC supply.**Products approved by this certificate are accepted for installation on all vessels classed by DNV GL.**Issued at **Høvik** on **2019-01-30**for **DNV GL**This Certificate is valid until **2021-01-29**.DNV GL local station: **Malmö**Approval Engineer: **Georgy Abramenko**

Marta Alonso Pontes
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-008042-14**
Certificate No: **TAE00001HD**
Revision No: **1**

Product description

Variable speed controller for asynchronous motor. Constant/Variable torque applications. Air and liquid cooled.

480 V Series:

Model	Max. output current [A]*	Normal duty (120%, 1 min. every 10 min)		Heavy duty (150%, 1 min every 10 min)		Frame size
		Power 400 V [kW]**	Rated current [A]	Power 400 V [kW]**	Rated current [A]	
VFX48-003	3.8	0.75	2.5	0.55	2.0	B
VFX48-004	6.0	1.5	4.0	1.1	3.2	
VFX48-006	9.0	2.2	6.0	1.5	4.8	
VFX48-008	11.3	3	7.5	2.2	6.0	
VFX48-010	14.3	4	9.5	3	7.6	
VFX48-013	19.5	5.5	13.0	4	10.4	
VFX48-018	27.0	7.5	18.0	5.5	14.4	
VFX48-026	39	11	26	7.5	21	C
VFX48-031	48	15	31	11	25	
VFX48-037	55	18.5	37	15	29.6	
VFX48-046	69	22	46	18.5	37	
VFX48-061	92	30	61	22	49	D
VFX48-074	111	37	74	30	59	
VFX48-090	108	45	90	37	72	E
VFX48-109	131	55	109	45	87	
VFX48-146	175	75	146	55	117	
VFX48-175	210	90	175	75	140	
VFX48-210	252	110	210	90	168	F
VFX48-228	300	110	228	90	182	
VFX48-250	300	132	250	110	200	
VFX48-295	354	160	295	132	236	
VFX48-300	360	160	300	132	240	G
VFX48-365	438	200	365	160	292	FA
VFX48-375	450	200	375	160	300	G
VFX48-430	516	220	430	200	344	H
VFX48-500	600	250	500	220	400	
VFX48-600	720	315	600	250	480	I
VFX48-650	780	355	650	315	520	
VFX48-750	900	400	750	355	600	J
VFX48-860	1032	450	860	400	688	
VFX48-1K0	1200	560	1000	450	800	KA
VFX48-1K15	1380	630	1150	500	920	
VFX48-1K25	1500	710	1250	560	1000	K
VFX48-1K35	1620	710	1350	600	1080	
VFX48-1K5	1800	800	1500	630	1200	L
VFX48-1K75	2100	900	1750	800	1400	
VFX48-2K0	2400	1120	2000	900	1600	M

Job Id: **262.1-008042-14**
 Certificate No: **TAE00001HD**
 Revision No: **1**

Model	Max. output current [A]*	Normal duty (120%, 1 min. every 10 min)		Heavy duty (150%, 1 min every 10 min)		Frame size
		Power 400 V [kW]**	Rated current [A]	Power 400 V [kW]**	Rated current [A]	
VFX48-2K25	2700	1250	2250	1000	1800	N
VFX48-2K5	3000	1400	2500	1120	2000	O

* Available during limited time and as long as allowed by the drive temperature

** Values applicable for 40 °C, to be modified for ships application at 45 °C. See under "Application / limitation".

525 V series:

Model	Max. output current [A]*	Normal duty (120%, 1 min. every 10 min)		Heavy duty (150%, 1 min every 10 min)		Frame size
		Power 525 V [kW]**	Rated current [A]	Power 525 V [kW]**	Rated current [A]	
VFX52-003	3.8	1.1	2.5	1.1	2.0	B
VFX52-004	6.0	2.2	4.0	1.5	3.2	
VFX52-006	9.0	3	6.0	2.2	4.8	
VFX52-008	11.3	4	7.5	3	6.0	
VFX52-010	14.3	5.5	9.5	4	7.6	
VFX52-013	19.5	7.5	13.0	5.5	10.4	
VFX52-018	27.0	11	18.0	7.5	14.4	C
VFX52-026	39	15	26	11	21	
VFX52-031	48	18.5	31	15	25	
VFX52-037	55	22	37	18.5	29.6	
VFX52-046	69	30	46	22	37	D
VFX52-061	92	37	61	30	49	
VFX52-074	111	45	74	37	59	

690 V Series:

Model	Max. output current [A]*	Normal duty (120%, 1 min. every 10 min)		Heavy duty (150%, 1 min every 10 min)		Frame size
		Power 690 V [kW]**	Rated current [A]	Power 690 V [kW]**	Rated current [A]	
VFX69-090	108	90	90	75	72	F69
VFX69-109	131	110	109	90	87	
VFX69-146	175	132	146	110	117	
VFX69-175	210	160	175	132	140	
VFX69-200	240	200	200	160	160	
VFX69-250	300	250	250	200	200	H69
VFX69-300	360	315	300	250	240	
VFX69-375	450	355	375	315	300	
VFX69-400	480	400	400	315	320	
VFX69-430	516	450	430	315	344	I69
VFX69-500	600	500	500	355	400	
VFX69-595	720	600	600	450	480	J69
VFX69-650	780	630	650	500	520	

Job Id: **262.1-008042-14**
 Certificate No: **TAE00001HD**
 Revision No: **1**

VFX69-720	864	710	720	560	576	
VFX69-800	960	800	800	630	640	
VFX69-905	1080	900	900	710	720	KA69
VFX69-995	1200	1000	1000	800	800	
VFX69-1K2	1440	1200	1200	900	960	K69
VFX69-1K4	1680	1400	1400	1120	1120	L69
VFX69-1K6	1920	1600	1600	1250	1280	M69
VFX69-1K8	2160	1800	1800	1400	1440	N69
VFX69-2K0	2400	2000	2000	1600	1600	O69
VFX69-2K2	2640	2200	2200	1700	1760	P69
VFX69-2K4	2880	2400	2400	1900	1920	Q69
VFX69-2K6	3120	2600	2600	2000	2080	R69
VFX69-2K8	3360	2800	2800	2200	2240	S69
VFX69-3K0	3600	3000	3000	2400	2400	T69

* Available during limited time and as long as allowed by the drive temperature

** Values applicable for 40 °C, to be modified for ships application at 45 °C. See under "Application / limitation".

In cases where multiple drives are installed in parallel an improved insulation resistance to ground may be required to avoid false earth fault detection. In such cases drives may be equipped with an optional high impedance DC link measurement board based on an opto coupler.

Application/Limitation

Supply voltage range:	230 - 480 or 500 - 690 V, 50/60 Hz
Voltage variation:	÷15 % + 10 % (steady state) at U ≥ 380 V ÷10 % + 10 % (steady state) at U = 230 V
Frequency range:	45 - 65 Hz
Output frequency:	0 - 400 Hz
Temperature range in operation:	0 - 40 °C (40 - 45 °C when derated 1 %/°C)
Temperature class:	A
Vibration class:	A
Humidity class:	A
EMC class*:	IEC 61800-3 To be used on EMC class A locations

The VFX must be regarded as a component. The actual installation shall be designed according to CG Drives & Automation Sweden AB Users Manual and according to the applicable DNV-GL Rules for the actual application. Drawings for the actual application are to be submitted for approval in each case. A product certificate is required in accordance with Rule paragraph Pt.4, Ch.8, Sec. 1, 2.3.1 (sizes ≥ 100 kW).

Frame sizes H69 to T69 / G to O are to be installed in an enclosure with an IP degree in accordance with DNV Rules w.r.t. location.

*Converters with conducted and radiated emission above the DNV-GL required limits can be installed in "special distribution zone" and "general power distribution zone", in accordance with IEC 60533 provided measures are taken to attenuate these effects on the distribution system, so the safe operation is assured. Planned EMC measures shall be submitted for approval prior to installation onboard. The EMC measures should be derived from an EMC analysis and plan in accordance with IEC 60533 Annex B and /or IEC 61800-3 Annex E.

Job Id: **262.1-008042-14**
Certificate No: **TAE00001HD**
Revision No: **1**

Type Approval documentation

Technical info:

"Technical data CG Drives & Automation Sweden AB doc. no 01-4428-01r2" undated, part 10 of Booklet "DNV SIZE E-K 690 V.

Technical data CG Drives & Automation Sweden AB doc. no 01-4428-01r2" undated, part 10 of Booklet "DNV SIZE E-K 480 V.

Schematic drawings, Template VFX_FDU48-1k5-6P MS dated 2010-06-30

Instruction manual Emotron FDU/VFX 2.0 Liquid Cooling, Emotron AB 01-4636-01r1

Instruction manual Emotron FDU 2.0 AC drive SW ver 4.3X, CG Drives & Automation, 01-5325-01r2

Test reports:

"DELTA Test report no. A506587 dated 2009-12-15 & "Binder no. 1 (part of CD rom "DNV Additional type tests dated 2010-03-10.) "DELTA Test report no. DANAK-1910574 dated 2009-08-26 & Serbert Trillingstechnik B.V.doc. no. M09.011-2009.7076 dated 2009-08-28, part 4 of Booklet "DNV SIZE E-K 690 V.

DECTRON test reports 06047 dated 2006-03-15, 07019 dated 2007-02-02, 07020 dated 2007-02-20, 07275 dated 2007-12-18 & 07276 dated 2007-12-19.

CG Drives & Automation Sweden AB doc. no "2.2.4 Protective impedance test – R40 doc", dated 2009-09-17; doc. no "2.2.9 Temperature rise 690 V – R61.doc", dated 2009-10-03; doc no. "5.2.4. Voltage unbalance and frequency variations – R50.doc" & 5.2.3 Voltage deviations dips and short interruptions – R5x.doc", dated 2009-03-17; KEMA test report 2097658.01-QUA/INC, dated 2007-01-31. UL test report "File no. E311216" dated 2008-04-29.

"DELTA report, ProjA506587", dated 2009-12-15.

"Serbert Trillingstechnik B.V. doc no. M10.001-2010.7017" dated 2010-01-26.

CG Drives & Automation Sweden AB report "Converter losses" dated 2010-01-29.

CG Drives & Automation, testreport "LC on stacked drive" dated 2014-03-26.

CG Drives & Automation, testreport on 2 x FDU69-720L 2014-02-28

Emotron type test report, 2.2.9 temperature rise 690V – R61 dated 2009-10-13

Description of High imp DC link measurement option board

Data Sheet: Precision Optically Isolated Voltage Sensor

Specification for drive transformer T60403-F5046-X006 dated 27.02.2007

CG Drives & Automation, Schematic insulated DC meas/standby supply Drwg no 01-6415-00 dated 2016-09-07

FDU-295, FDU-365 test reports and documentation ref. NPS job 262.1-008042-14.

Tests carried out

Visual inspection, Performance/heat run, Power supply failure, Power supply variations, Voltage/frequency variation, Vibration, Dry heat, Damp heat, Insulation resistance, High voltage, IP degree.

EMC: The following tests are in accordance with the DNV CN2.4/ IEC 61800-3: Electrical fast transient (Burst), electrical slow transient (Surge), RF-common mode Voltage,


radiated RF-electromagnetic fields, electric discharge (ESD), radiated and conducted emission. (See under application limitation).

Marking of product

Type designation – Voltage – Current

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.



Job Id: **262.1-008042-14**
Certificate No: **TAE00001HD**
Revision No: **1**

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine Tests (RT) checked (if not available tests according to RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE