



NB1L Residual Current Operated Circuit Breaker with over-current protection (Magnetic)

1. General

1.1 Function

Personnel and fire protection: Cable and line protection against overload and short-circuits.

1.2 Selection

Rated residual operating current

$I_{\Delta n} \leq 30$ mA: additional protection in the case of direct contact.

$I_{\Delta n} \leq 300$ mA: preventative fire protection in the case of ground fault currents.

Tripping class

AC class

Tripping is ensured for sinusoidal, alternating currents, whether they be quickly applied or slowly increase.

A class

Tripping is ensured for sinusoidal, alternating residual currents as well as for pulsed DC residual currents, whether they be quickly applied or slowly increase.

Tripping curve

B curve (3-5 I_n) protection and control of the circuits against overloads and short-circuits; protection for people and big length cables in TN and IT systems.



C curve (5-10 I_n) protection and control of the circuits against overloads and short-circuits; protection for resistive and inductive loads with low inrush current.

1.3 Approvals and certificates

Detailed information, please refer to Certificates Table on the last page.

2. Technical data

2.1 Curves



2.2

	Standard	IEC/EN 61009-1			
Electrical features	Type (wave form of the earth leakage sensed)	AC, A			
	Thermo-magnetic release characteristic	B, C			
	Rated current I_n	A	MCB+add-on RCCB block	1, 2, 3, 4, 6, 8, 10, 13, 16, 20, 25, 32, 40	50, 63
			Combined	1-25/6-40	
	Poles		MCB+add-on RCCB block	1P+N, 2P, 3P, 3P+N, 4P	
			Combined	1P+N, 2P	
	Rated voltage U_e	V	230/400~240/415		
	Rated sensitivity $I_{\Delta n}$	A	0.03, 0.1, 0.3		
	Rated residual making and breaking capacity $I_{\Delta m}$	A	500 ($I_n \leq 40A$)		
			630 ($I_n > 40A$)		
	Rated short-circuit capacity I_{cn}	A	6,000/10,000		
	Break time under $I_{\Delta n}$	S	≤ 0.1		
	Rated frequency	Hz	50/60		
Rated impulse withstand voltage $(1.2/50)U_{imp}$	V	6,000			
Dielectric TEST voltage at ind. Freq. for 1min	kV	2			
Insulation voltage U_i		500			
Pollution degree		2			
Mechanical features	Electrical life	2,000			
	Mechanical life	20,000			
	Contact position indicator	Yes			
	Protection degree	IP20			
	Ambient temperature (with daily average $\leq 35^\circ C$)	$^\circ C$	-5...+40		
Storage temperature	$^\circ C$	-25...+70			
Installation	Terminal connection type	Cable/U-type busbar/Pin-type busbar			
	Terminal size top/bottom for cable	mm^2	25		
		AWG	18-3		
	Terminal size top/bottom for busbar	mm^2	10		
		AWG	18-8		
	Tightening torque	N-m	2		
		In-lbs.	18		
Mounting	On DIN rail EN 60715 (35mm) by means of fast clip device				
Connection	From top and bottom (for combined type)				
	From top (MCB+add-on RCCB block)				



2.3 Temperature derating


The maximum permissible current in a circuit breaker depends on the ambient temperature where the circuit breaker is placed. Ambient temperature is the temperature inside the enclosure or switchboard in which the circuit breakers are installed.

The reference temperature is 30°C

Temperature	-10°C	0°C	10°C	20°C	30°C	40°C	50°C	60°C
Temperature compensation coefficient of rated current	1.20	1.15	1.10	1.05	1.00	0.95	0.90	0.85


3. Overall and mounting dimensions (mm)

MCB+add-on RCCB block



Number of poles	Overall dimensions A (mm)	
	1~40A	50~63A
1P+N	45 ⁰ _{-0.62}	54 ⁰ _{-0.74}
2P	63 ⁰ _{-0.74}	72 ⁰ _{-0.74}
3P	108 ⁰ _{-1.4}	117 ⁰ _{-1.4}
3P+N	108 ⁰ _{-1.4}	117 ⁰ _{-1.4}
4P	126 ⁰ _{-1.6}	135 ⁰ _{-1.6}
B(mm)		
1P+N	27 ⁰ _{-0.52}	36 ⁰ _{-0.62}
2P	27 ⁰ _{-0.52}	36 ⁰ _{-0.62}
3P	54 ⁰ _{-1.20}	63 ⁰ _{-1.2}
3P+N	54 ⁰ _{-1.20}	63 ⁰ _{-1.2}
4P	54 ⁰ _{-1.20}	63 ⁰ _{-1.2}

Combined



1P+N

2P